

SAMPLE - NOT A REAL SDS

Placeholder created for the Andari Safety Program demo. Replace with the manufacturer's Safety Data Sheet before use.

SAFETY DATA SHEET: Diesel Fuel No. 2 (ULSD)

Section 1. Identification

Diesel Fuel No. 2 (ULSD) (EX-ULSD-2)

Supplier: Example Petroleum Co., 125 Industrial Pkwy, Springfield, ST 00001, (555) 010-2011

Emergency: (555) 019-9001

Section 2. Hazard identification

Signal word: Danger

Pictograms: GHS02, GHS07, GHS08, GHS09

H226 Flammable liquid and vapor.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H332 Harmful if inhaled.

H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements:

P201 Obtain special instructions before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260 Do not breathe dust/fume/gas/mist/vapors/spray.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P331 Do NOT induce vomiting.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P370+P378 In case of fire: Use dry chemical, CO₂, water spray or foam to extinguish.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national regulations.

Section 3. Composition

Fuels, diesel, No. 2 CAS 68476-34-6 95-100%

Naphthalene CAS 91-20-3 <0.5%

Section 4. First aid

Swallowed: do NOT induce vomiting, call a poison center. Skin: wash with soap and water. Inhaled: move to fresh air.

Sections 5-16

Not included in this sample. See the manufacturer's SDS.

Revision date: 2024-06-12